

XP 2040 PART B

Page 1 Issued: 27/06/2005 Revision No: 2

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: XP 2040 PART B

Company name: Chemique Adhesives & Sealants Ltd Unit 21 Empire Close Aldridge West Midlands WS9 8UR United Kingdom Tel: +44 (0) 1922 459 321 Fax: +44 (0) 1922 459 321

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: NONYLPHENOL 1-10% EINECS: 246-672-0 CAS: 25154-52-3 [Xn] R22; [C] R34; [N] R50/53

- BENZYL ALCOHOL 10-30% EINECS: 202-859-9 CAS: 100-51-6 [Xn] R20/22
- 4,4'-ISOPROPYLIDENEDIPHENOL 10-30% EINECS: 201-245-8 CAS: 80-05-7 [Xi] R37; [Xi] R41; [Sens.] R43; [Xn] R62
 M-XYLYLENEDIAMINE 30-50%
 - EINECS: 216-032-5 CAS: 1477-55-0
 - [Xn] R20/22; [C] R34; [Sens.] R43; [-] R52/53

3. HAZARDS IDENTIFICATION

Main hazards:Harmful by inhalation and if swallowed. Causes burns. May cause sensitisation by skin contact.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Possible risk of impaired fertility.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact:	Blistering may occur. Progressive ulceration will occur if treatment is not immediate.
Eye contact:	Corneal burns may occur. May cause permanent damage.
Ingestion:	Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding
	from the mouth or nose.
Inhalation:	There may be shortness of breath with a burning sensation in the throat. Exposure may cause
	coughing or wheezing.

SAFETY DATA SHEET XP 2040 PART B

Skin contact.	Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the
Skii contact.	affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to
	hospital if there are burns or symptoms of poisoning.
Eye contact:	
-	Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
Ingestion:	Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10
	minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If
	unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon
.	as possible.
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and
	breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies
	down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available.
	Transfer to hospital as soon as possible.
FIRE-FIGHTING MEAS	URES
Extinguishing media:	Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool
	containers.
Exposure hazards:	Corrosive. In combustion emits toxic fumes.
Protection of fire-fighters:	Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin
	and eyes.
ACCIDENTAL RELEAS	E MEASURES
Personal precautions:	Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from
i ci sonai precautions.	danger point. Mark out the contaminated area with signs and prevent access to unauthorised
	personnel Do not attempt to take action without suitable protective clothing - see section 8 of
	personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid
vironmental processions.	SDS. Turn leaking containers leak-side up to prevent the escape of liquid.
nvironmental precautions:	SDS. Turn leaking containers leak-side up to prevent the escape of liquid. Do not discharge into drains or rivers. Contain the spillage using bunding.
nvironmental precautions: Clean-up procedures:	SDS. Turn leaking containers leak-side up to prevent the escape of liquid.Do not discharge into drains or rivers. Contain the spillage using bunding.Clean-up should be dealt with only by qualified personnel familiar with the specific substance.
-	SDS. Turn leaking containers leak-side up to prevent the escape of liquid.Do not discharge into drains or rivers. Contain the spillage using bunding.Clean-up should be dealt with only by qualified personnel familiar with the specific substance.Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by
Clean-up procedures:	SDS. Turn leaking containers leak-side up to prevent the escape of liquid.Do not discharge into drains or rivers. Contain the spillage using bunding.Clean-up should be dealt with only by qualified personnel familiar with the specific substance.Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.
Clean-up procedures:	SDS. Turn leaking containers leak-side up to prevent the escape of liquid.Do not discharge into drains or rivers. Contain the spillage using bunding.Clean-up should be dealt with only by qualified personnel familiar with the specific substance.Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.
Clean-up procedures: HANDLING AND STOR	SDS. Turn leaking containers leak-side up to prevent the escape of liquid.Do not discharge into drains or rivers. Contain the spillage using bunding.Clean-up should be dealt with only by qualified personnel familiar with the specific substance.Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.
Clean-up procedures: HANDLING AND STOR	 SDS. Turn leaking containers leak-side up to prevent the escape of liquid. Do not discharge into drains or rivers. Contain the spillage using bunding. Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.
Clean-up procedures: HANDLING AND STOR	 SDS. Turn leaking containers leak-side up to prevent the escape of liquid. Do not discharge into drains or rivers. Contain the spillage using bunding. Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. AGE Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do

XP 2040 PART B

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients:	4,4'-ISOPROPYLIDENEDIPHENOL	
	TWA 5 mg/m3 STEL 5 mg/m3	
Engineering measures:	Ensure there is sufficient ventilation of the area.	
Respiratory protection:	Self-contained breathing apparatus must be available in case of emergency.	
Hand protection:	Impermeable gloves. Nitrile gloves.	
Eye protection:	Tightly fitting safety goggles. Ensure eye bath is to hand.	
Skin protection:	Impermeable protective clothing.	

9. PHYSICAL AND CHEMICAL PROPERTIES

State:	Liquid
Colour:	Yellow-brown
Odour:	Characteristic odour
Oxidising:	Non-oxidising (by EC criteria)
Solubility in water:	Not miscible
Viscosity:	Viscous
Viscosity value:	700cps
Boiling point/range°C:	200
Flash point°C:	121
Relative density:	1.07 @ 20'C
pH:	12

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to avoid:	Heat. Static electricity discharge
Materials to avoid:	Strong oxidising agents. Strong acids.
Haz. decomp. products: In combustion emits toxic fumes. In combustion emits toxic fumes of carbon dioxide / carbon	
	monoxide. In combustion emits toxic fumes of nitrogen oxides.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients:	NONYLPHENOL
------------------------	-------------

- ORL MUS LD50 1231 mg/kg
- ORL RAT LD50 580 mg/kg
- BENZYL ALCOHOL IVN RAT LD50 53 mg/kg ORL MUS LD50 1360 mg/kg
- ORL RAT LD50 1230 mg/kg
- 4,4'-ISOPROPYLIDENEDIPHENOL

Page 3

XP 2040 PART B

12. ECOLOGICAL INFORMATION		
Routes of exposure:	Refer to section 4 of SDS for routes of exposure and corresponding symptoms.	
Chronic toxicity:	Danger of cumulative effects in contact with the skin.	
	ORL RAT LD50 3250 mg/kg	
	ORL MUS LD50 2400 mg/kg	

Mobility:	Non-volatile.
Persistence and degradability:	Only slightly biodegradable.
Bioaccumulative potential:	Slightly bioaccumulable.
Other adverse effects:	Toxic to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no:	2735 ADR Class:	8
Packing group:	III Classification code:	C7
Shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (M-XYLYLENEDIAMINE; NON	NYLPHENOL)
Labelling:	8 Hazard ID no:	80
	CORROSIVE	
IMDG / IMO		
UN no:	2735 Class:	8
Packing group:	III EmS:	F-A,S-B
Marine pollutant:	. Labelling:	8
IATA / ICAO		
UN no:	2735 Class:	8
Packing group:	III Packing instructions:	818(P&CA); 820(CAO)
Labelling:	8	
15. REGULATORY INFOR	MATION	
Hazard symbols:	Dangerous for the environment.	

Corrosive.

XP 2040 PART B

¥_2	5- J
-----	------

Risk phrases:	R20/22: Harmful by inhalation and if swallowed.
	R34: Causes burns.
	R43: May cause sensitisation by skin contact.
	R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic
	environment.
	R62: Possible risk of impaired fertility.
Safety phrases:	S23: Do not breathe fumes.
	S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical
	advice.
	S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.
	S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label
	where possible).
	S61: Avoid release to the environment. Refer to special instructions / safety data sheets.
Water hazard class:	
Note:	The regulatory information given above only indicates the principal regulations specifically
	applicable to the product described in the safety data sheet. The user's attention is drawn to
	the possible existence of additional provisions which complete these regulations. Refer to all
	applicable national, international and local regulations or provisions.
16. OTHER INFORMATIO	N
Risk phrases used in s.2:	R22: Harmful if swallowed.
	R34: Causes burns.
	R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic
	environment.
	R20/22: Harmful by inhalation and if swallowed.
	R37: Irritating to respiratory system.
	R41: Risk of serious damage to eyes.
	R43: May cause sensitisation by skin contact.
	R62: Possible risk of impaired fertility.
	R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic
	environment.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive and shall
	be used only as a guide. This company shall not be held liable for any damage resulting from
	handling or from contact with the above product.

Page 5