



# UNIVERSAL MAINS WATER ADAPTOR KIT FITTING INSTRUCTIONS

## CONTENTS



Part No.  
ES2310

Flow Valve assembly for use on  
Aquaroll, Roly Poly and Aquarious.



Part No.  
ES2330

7.5 Metre Food Grade Hose,  
fitted with Hose connections attached.



Part No.  
ES2322

2 x Metric / Imperial Tap Connectors



Hose Extension Adaptors



Additional 2 caps supplied for use on  
WaterHog, Aqua Caddy, and the NEW fit  
51 litre WaterHog.

## FITTING INSTRUCTIONS - for Aquaroll, Roly Poly and Aquarious

- Make sure your water carrier is standing in an upright position.
- Unscrew the centre cap and place it in a safe place for use when not using a super pitch or service pitch.
- Insert your float valve assembly into the centre opening and tighten the cap.
- View from the opening on the top and adjust the position of your float valve until the water outlet is in a downward position and then tighten the exterior locking nut.



- Connect one of the tap connectors to the float valve assembly and then connect one of the ends from the hose
- Attach a tap connector to your super pitch site water tap and attach the remaining end of the hose to this connection.
- Turn on the tap and the water will fill your container half full and will maintain a constant amount of water.
- Please ensure that you turn off the service pitch tap before you disconnect your assembly.

## FITTING INSTRUCTIONS - for WaterHog and Aqua Caddy

- Unscrew the cap already assembled to the Float Valve and replace with the additional cap provided and follow the instructions as above.



Replacement Aquaroll  
Water Tank Cap  
(Sold Separately)  
Part No. ES2300



Replacement NEW fit  
51 Litre WaterHog Cap  
(Sold Separately)  
Part No. ES2305

If you have any further  
questions please  
contact us on the  
Telephone number  
below.

Please keep these  
instructions for your  
future reference

Tel: 01422 313455 Fax: 01422 313550  
www.plsgroup.co.uk Email: info@plsgroup.co.uk