



FA6620 10 YEAR SMOKE ALARM - Optical, Sealed for Life Battery

Sensor type	Optical
Battery type	Sealed for life lithium battery



- Battery powered optical smoke alarm
- Reduces nuisance cooking alarms
- Large central test button
- Sleep Easy - silence the low battery chirp for 8 hours
- Operating Light (RED) - flashes approximately every 40 seconds confirming alarm is powered
- Low Battery Warning - 'beeps' approximately every 40 seconds when the alarm needs replacing
- Loud 85 Decibel Piezo Electric Alarm
- Suitable for leisure accommodation vehicles (LAV)
- Easy Installation - fixings supplied
- Quiet test function supports discreet testing at a lower volume when compared to standard alarms




22
1116
EN 14604:2005+AC:2008
Smoke Alarm Devices
FSTDOP21006



22
0832
EN 14604:2005+AC:2008
Smoke Alarm Devices
FSTDOP21007

Technical Specification

Dimensions	118.1mm (diameter) x 31.5mm (depth)	
Battery	10 year sealed for life lithium battery	
Sensor Technology	Optical	
Alarm sound level	85dB(A) at 3m (minimum)	
Installation positions	Wall/Ceiling	
Operating temperature	+4°C to +38°C	
Operating humidity	Up to 90% RH (non condensing)	
Storage temperature	-20°C to +60°C	
Storage humidity	Up to 93% RH (non condensing)	
Warranty	5 Years	
Certified to	EN 14604:2005+AC:2008	
Weight	138g	
Leisure Accomodation Vehicles	Yes	