

PRODUCT DATA SHEET

CARAVAN TAPE SUPER		
Version No.2	Revision Date: 02/01/2019	Page 1 of 2

DESCRIPTION

Caravan Tape Super is a high performance butyl tape, designed for use in caravan construction.

KEY FEATURES

Excellent adhesion to a wide range of substrates.	Good UV resistance
Highly conformable	Easy and accurate to use with little waste and no mess.
Remains flexible throughout its service life.	

USES

For sealing in many caravan applications, such as roof-to-wall joints, behind rails, and around door and window frames.

PERFORMANCE

	UNIT	NOMINAL VALUE	TEST METHOD
DynamicTensile Adhesion	N/cm ²	22	H5
Dynamic Shear Adhesion	N/cm ²	19	H15
90 ° Peel Adhesion	N/cm	12	H48
180 ° Peel Adhesion	N/cm	21	H41
Specific Gravity	g/cm ³	1.5	H6
Service Temperature Range	°C	-40 to +90	



PRODUCT DATA SHEET

CARAVAN TAPE SUPER

Version No.2

Revision Date: 02/01/2019

Page 2 of 2

APPLICATION

PROPERTIES

Application temperature range: +5°C to +40°C

Shelf life: 24 months when stored flat in original packaging in cool, dry conditions.

INSTRUCTIONS

Surface preparation: All surfaces should be clean, dry and free from frost, grease and loose materials. When cleaning contaminated substrates recommend that propan-2-ol (IPA) is used and allowed to dry prior to the application of the butyl tape.

Application: Apply direct from the reel onto one surface and press sufficiently along its whole length to achieve good initial adhesion. Remove backing paper and offer other surface to the tape and push firmly to seal across the joint.

PACKAGING

The product is normally supplied as an extruded strip on a siliconised release paper. A wide range of dimensions can be supplied. Product dimensions will determine the number of rolls per carton.

Available colours: Black, grey or white.

TOLERANCES

Rectangular sections:

Thickness $\pm 10\%$

Width: up to 25mm $\pm 1\text{mm}$

26mm to 100mm $\pm 2\text{mm}$

over 100mm $\pm 3\text{mm}$

Bead sections:

Thickness $\pm 10\%$

Width $\pm 10\%$

GENERAL

The information given in this product data sheet is based on laboratory tests and experience which we believe to be correct. Properties quoted are typical and do not therefore constitute a specification. In view of the wide range and variability of substrates, we would advise that our product should be tested by the user to establish suitability for its intended application. E &OE.

