

Specifications	 <p data-bbox="622 480 871 504">Pro Underseat 135Ah</p>	 <p data-bbox="1196 480 1462 504">Pro Underseat 200Ah</p>	 <p data-bbox="1783 480 2045 504">Pro Underseat 500Ah</p>
Battery Cell Type	Lithium Iron Phosphate	Lithium Iron Phosphate	Lithium Iron Phosphate
Rated Capacity (0.5C, 25°C)	135Ah	200Ah	500Ah
Nominal Voltage	12.8V	12.8V	12.8V
Voltage Range	10V to 14.8V	10V to 14.8V	10V to 14.8V
Cycle Life (0.5C, 25°C)	4000 Cycles (80% DOD)	4000 Cycles (80% DOD)	3500 Cycles (80% DOD)
Dimension	13.98 x 6.97 x 7.48 in / 355 x 177 x 190 mm	14.37 x 8.86 x 7.48 in / 365 x 225 x 190 mm	14.0 x 13.8 x 7.8 in / 355 x 350 x 198 mm
Weight	31.97 lbs / 14.5 kg	50.71 lbs / 23.0 kg	110.23 lbs / 50 kg
Connection Method	4S4P	4S4P	Parallel (Up to 8 batteries)
Terminal Bolt Size	/	M8 x 1.25 x 16 mm	Long Terminal Bolt: M8 x 1.25 x 16 mm
Recommended Terminal Torque	/	88.5 inch·lbs to 106.2 inch·lbs / 10 N·m to 12 N·m	70.8 inch·lbs / 8 N.m
Protection Rating	IP65	IP65	IP65
Certification	MSDS, UN383, CE, and RoHS	MSDS, UN383, CE, and RoHS	MSDS, UN383, CE, and RoHS
Warranty	5 Years	5 Years	5 Years