

Fire Blanket Product Information

All of our Premium Range fire blankets, including the 1.1m x 1.1m Square Pack fire blanket have the essential performance requirement in that they must extinguish a cooking oil fire (as detailed in BS EN 1869:2019). To achieve this, the fire blanket must be flexible, with good draping qualities, to eliminate oxygen from the burning oil and to allow the oil to cool gradually to below its self-ignition temperature. It should not reignite when the blanket is removed after 17 minutes.

In addition, the fire blanket must now extinguish a flammable fuel fire (as detailed in BS EN 1869:2019). To achieve this, the fire blanket must be flexible, eliminate oxygen from the burning fuel. It should not reignite when the blanket is removed after 4 minutes.

Our 1.1m x 1.1m Premium fire blanket has a unique 3-ply material; two layers of woven glass fibre fabric with an inner layer of fire retardant film and it is this construction that is at the forefront of the fire blankets unblemished safety record. It is a longstanding performance record unrivalled in the industry and now the first to be approved to the 2019 product standard.

Compact and practical, the attractive one-piece Square Pack holder is available in white.

For added value, we also offer the option of corporate branded fire blanket labels... a fantastic way to promote the corporate image of your organisation.

ABC Powder



The 600g ABC Powder aerosol extinguisher is Kitemark certified to BS 6165. The stored pressure ABC powder aerosol extinguisher is suitable for use on Class A, B and C fires meaning that it's ideally suited for domestic and leisure use. Also highly effective against petrol and volatile liquids, which make them ideal for vehicle protection.

- › Aluminium lightweight body.
- › Controlled discharge.
- › Available in red or silver body.
- › Mounting bracket included.
- › No formal maintenance required.
- › Not suitable for use on deep fat fryer fires.



MADE IN THE UK



FULLY CERTIFIED



5 YEAR GUARANTEE



Mounting
bracket
included

› AEABC600R : 600g ABC Powder



› AEABC600S : 600g ABC Powder



BOATS & MARINE



DOMESTIC



AUTOMOBILES



CARAVANS

Product Certification and Specification



KM 543762
BS 6165



› EXTINGUISHER :	600g ABC Powder
› PRODUCT CODE :	AEABC600R
› MEDIUM :	ABC 40 Powder
› PROPELLANT :	Nitrogen gas
› FIRE RATING :	3A 21B C
› OPERATING TEMPERATURE :	-20°C to +50°C
› AVERAGE DISCHARGE TIME :	6 seconds
› RANGE OF DISCHARGE :	2-3 metres
› HEIGHT & DIAMETER :	Height 287mm Diameter 66mm
› FILLED WEIGHT (with bracket) :	0.76kg
› CYLINDER COLOUR :	Red

600g ABC Powder
AEABC600R
ABC 40 Powder
Nitrogen gas
3A 21B C
-20°C to +50°C
6 seconds
2-3 metres
Height 287mm Diameter 66mm
0.76kg
Red

600g ABC Powder
AEABC600S
ABC 40 Powder
Nitrogen gas
3A 21B C
-20°C to +50°C
6 seconds
2-3 metres
Height 287mm Diameter 66mm
0.76kg
Silver