

XP 2460 PART B

Page 1 Issued: 16/06/2005 Revision No: 3

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: XP 2460 PART B

Synonyms: XP 2460 PARTS A & B

Company name: Chemique Adhesives & Sealants Ltd

Unit 21

Empire Close

Aldridge

West Midlands

WS9 8UR

United Kingdom

Tel: +44 (0) 1922 459 321 Fax: +44 (0) 1922 452 833

Emergency tel: +44 (0) 1922 459 321

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: DIPHENYLMETHANE-4,4'-DI-ISOCYANATE 30-50% EINECS: 202-966-0 CAS: 101-68-8 [Xn] R20; [Xi] R36/37/38; [Sens.] R42/43

coughing or wheezing.

3. HAZARDS IDENTIFICATION

Main hazards: Harmful by inhalation. Irritating to eyes, respiratory system and skin. May cause sensitisation by inhalation and skin contact.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact:There may be irritation and redness at the site of contact.Eye contact:There may be irritation and redness. The eyes may water profusely.Ingestion:There may be soreness and redness of the mouth and throat.Inhalation:There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause

4. FIRST AID MEASURES (ACTION)

Skin contact:Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash
immediately with plenty of soap and water.Eye contact:Bathe the eye with running water for 15 minutes. Consult a doctor.Ingestion:Wash out mouth with water. Consult a doctor.Inhalation:Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool

containers.

XP 2460 PART B

-	In combustion emits toxic fumes.	
Protection of fire-fighters:	Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin	
	and eyes.	
6. ACCIDENTAL RELEAS	SE MEASURES	
Personal precautions:	Refer to section 8 of SDS for personal protection details. If outside do not approach from	
	downwind. If outside keep bystanders upwind and away from danger point. Mark out the	
	contaminated area with signs and prevent access to unauthorised personnel. Turn leaking	
	containers leak-side up to prevent the escape of liquid.	
Environmental precautions:	Do not discharge into drains or rivers. Contain the spillage using bunding.	
Clean-up procedures:	Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by	
	an appropriate method.	
7. HANDLING AND STORAGE		
Handling requirements:	Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do	
	not handle in a confined space. Avoid the formation or spread of mists in the air.	
Storage conditions:	Store in cool, well ventilated area. Keep container tightly closed.	
Suitable packaging:	Must only be kept in original packaging.	
8. EXPOSURE CONTROL	S / PERSONAL PROTECTION	
Hazardous ingredients:	DIPHENYLMETHANE-4,4'-DI-ISOCYANATE	
	TWA 0.02 mg/m3 STEL 0.07 mg/m3	
Engineering measures:	Ensure there is sufficient ventilation of the area.	
Respiratory protection:	Self-contained breathing apparatus must be available in case of emergency.	
Hand protection:	Protective gloves. Nitrile gloves.	
Eye protection:	Safety glasses. Ensure eye bath is to hand.	
Skin protection:	Protective clothing.	
9. PHYSICAL AND CHEM	ICAL PROPERTIES	
State:	Liquid	
Colour:	Yellow-brown	
Odour:	Barely perceptible odour	
Oxidising:	Non-oxidising (by EC criteria)	
Solubility in water:	Reacts with water.	
Viscosity:	Viscous	
Viscosity value:	200cps	
Flash point°C:	>200	
Relative density:	1.23 @ 20'C	

XP 2460 PART B

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to avoid:	Heat. Moist air.
Materials to avoid:	Strong oxidising agents. Strong acids. Amines.
Haz. decomp. products:	In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients:	DIPHENYLMETHANE-4,4'-DI-ISOCYANATE
	ORL MUS LD50 2200 mg/kg
	ORL RAT LD50 9200 mg/kg
Chronic toxicity:	May cause sensitisation by skin contact.
Routes of exposure:	Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility:Readily absorbed into soil.Persistence and degradability:Biodegradable.Bioaccumulative potential:No bioaccumulation potential.Other adverse effects:Harmful to soil organisms.

13. DISPOSAL CONSIDERATIONS

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: -

Shipping name: NOT CLASSIFIED AS DANGEROUS IN THE MEANING OF TRANSPORT REGULATIONS.

IMDG / IMO

UN no: -

IATA / ICAO

UN no: -

15. REGULATORY INFORMATION

Hazard symbols: Harmful.



XP 2460 PART B

Risk phrases:	R20: Harmful by inhalation.	
	R36/37/38: Irritating to eyes, respiratory system and skin.	
	R42/43: May cause sensitisation by inhalation and skin contact.	
Safety phrases:	S23: Do not breathe fumes.	
	S24: Avoid contact with skin.	
	S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical	
	advice.	
	S37: Wear suitable gloves.	
	S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label	
	where possible).	
	S63: In case of accident by inhalation, remove casualty to fresh air and keep at rest.	
Precautionary phrases:	Contains isocyanates. See information supplied by the manufacturer.	
Water hazard class:		
Note:	The regulatory information given above only indicates the principal regulations specifically	
	applicable to the product described in the safety data sheet. The user's attention is drawn to	
	the possible existence of additional provisions which complete these regulations. Refer to all	
	applicable national, international and local regulations or provisions.	
16. OTHER INFORMATION		
Disk whereas wood in a 2.	D20. Hamifal ha inhalation	

Risk phrases used in s.2:	R20: Harmful by inhalation.
	R36/37/38: Irritating to eyes, respiratory system and skin.
	R42/43: May cause sensitisation by inhalation and skin contact.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive and shall
	be used only as a guide. This company shall not be held liable for any damage resulting from
	handling or from contact with the above product.

Page 4